

Customised Granulators & Cutters


Steel series



Granulator housing	High-carbon steel
Motor standard	Customised, 1400/2800 rpm
Power	3 Phase, 230-460V, 50-60 Hz
Nom. amperage	4,00A
Fuse	10 Amp.
Knives	Hard-metal
Inlet/outlet width	55 to 520 mm (2.1" to 20.5")
Inlet/outlet height	55 to 70 mm (2.1" to 2.7")
Piping	Customised
Transmission	Direct coupling
Colour	Metal
Noise level	60 dB (A)
Minimum thickness	20 microns (0.0007")

Customised to application with inlet/outlet width from 55 to 520 mm (2.1" to 20.5") and height from 55 to 70 mm (2.1" to 2.7").

Stainless series



Granulator housing	Stainless steel
Motor standard	Customised, 1400/2800 rpm
Power	3 Phase, 230-460V, 50-60 Hz
Nom. amperage	4,00A
Fuse	10 Amp.
Knives	Hard-metal
Inlet/outlet width	55 to 520 mm(2.1" to 20.5")
Inlet/outlet height	55 to 70 mm (2.1" to 2.7")
Piping	Customised
Transmission	Direct coupling
Colour	Metal
Noise level	60 dB (A)
Minimum thickness	20 microns (0.0007")

Customised to application with inlet/outlet width from 55 to 520 mm (2.1" to 20.5") and height from 55 to 70 mm (2.1" to 2.7").